

Poly Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio

Active

830A1AA

NI

Specifications

All Specs

Aspect ratio	16:9
Audio	Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression; Comfort noise generation; DTMF tone generation (RFC 2833 and in-band); Low delay audio packet transmission; Adaptive jitter buffers
Audio codecs	G.711 (A-law and μ -law); G.722; G.722.1; G.722.1C; G.729AB; G.719; Polycom® Siren™ 7; Siren™ 14; iLBC; OPUS
Cartons per layer	4
Cartons per pallet	12
Certifications and compliances	AS/NZS 60950-1; AS/NZS 62368-1-17; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-1-14; CE Mark; CISPR22 Class B; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.9.1; ETSI EN 300 330; ETSI EN 301 893 v1.7.1; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1
Certified collaboration software	Microsoft Teams; Skype for Business
Color	Black
Country of origin	Made in China or Mexico
Dimensions (W x D x H)	38.3 x 7.5 x 33.2 cm
Display features	On-screen virtual keyboard
Display size (diagonal)	12.7 cm (5")
ECCN	5A992
Energy star certified	ENERGY STAR® certified
Headset and handset compatibility	Bluetooth® headset compatibility
HTS code	8517180050
Layers per pallet	3
Management Software	Poly Zero Touch Provisioning; RealPresence Resource Manager (v. 10.1 or above) based provisioning; Polycom Device Management Service for Enterprise (PDMS-E); Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management; SDP
Manufacturer product number	2200-86640-019
Manufacturer Warranty	Poly standard one-year limited warranty

Material Type for item	FERT
Microphone type	Three cardioid microphones
Multiple order quantity	5
Native resolution	720 x 1280
Network protocols, supported	DHCP VLAN discovery; LLDP-MED for VLAN discovery; FTP/TFTP/HTTP/HTTPS server-based central provisioning; Manual or dynamic host configuration protocol (DHCP) network setup; QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP; Time and date synchronization using SNTP; Provisioning and call server redundancy support
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Package dimensions (W x D x H)	48.3 x 11.5 x 39.4 cm
Package weight	300 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
Panel technology	Color LCD
Ports	1 USB 2.0 Type-A (for USB battery charging); 1 USB 2.0 Micro-B (for USB audio device); 2 RJ-45 (10/100/1000BASE-TX Mbps)
Power	LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4); LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment
Products per pallet	60
Products per pallet layer	20
Registration required	No
Security management	802.1X Authentication and EAPOL Media encryption via SRTP; Digest authentication; Encrypted configuration files; HTTPS secure provisioning; Password login; Support for signed software executables; Support for URL syntax with password; Transport Layer Security (TLS); Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2); FIPS 140-2 compliant cryptographic module
Sensitivity (speaker)	92 dB
Special features	Unicode UTF-8 character support
Storage temperature range	-20 to 70 °C
Telephony and call handling features	Bundled with Polycom UC Software: Corporate Directory Access using LDAP; Call timer and call waiting; Call transfer, hold, divert (forward), park, pickup; Called, calling, connected party information; Distinctive incoming call treatment/call waiting; Do not disturb function; Local configurable digit map/dial plan; Local five-way audio conferencing; Shared call/bridged line appearance; Visual Conference Management; Up to 3 lines (maximum one Skype for Business and Microsoft Teams); Daisy-chain up to four; One-touch speed dial, redial and meeting join
Touch-enabled	Gesture-based, multi-touch capable touchscreen

UNSPSC code	43191511
VoIP features	IETF SIP (RFC 3261 and companion RFCs)
Weight	950 g
What's in the box	Setup sheet; Console; Network (LAN) cable-CAT-5E; Cable wrap; Tactile overlay for improved accessibility
Wireless range	Up to 6.1 m

Logistics

ECCN	5A992
HTS code	8517180050
What's in the box	Setup sheet; Console; Network (LAN) cable-CAT-5E; Cable wrap; Tactile overlay for improved accessibility
Package dimensions (W x D x H)	48.3 x 11.5 x 39.4 cm
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Dimensions (W x D x H)	38.3 x 7.5 x 33.2 cm
Country of origin	Made in China or Mexico
Cartons per layer	4
Cartons per pallet	12
Multiple order quantity	5
Layers per pallet	3
Products per pallet	60
Products per pallet layer	20
Manufacturer product number	2200-86640-019
Material Type for item	FERT
UNSPSC code	43191511
Package weight	300 g
Pallet weight	357 kg
Weight	950 g

Specifications

[1] Requires full Class 4 power input on LAN IN for operation

Legal disclaimer