

Poly Trio 8300 IP Conference Phone and PoE-enabled

Discontinued

849A0AA

NI

Specifications

All Specs

Aspect ratio	16:9
Audio	Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression; Comfort noise generation; DTMF tone generation (RFC 2833 and in-band); Low delay audio packet transmission; Adaptive jitter buffers
Audio codecs	G.711 (A-law and μ -law); G.722; G.722.1; G.722.1C; G.729AB; G.719; SILK; Polycom® Siren™ 7; Siren™ 14; iLBC; OPUS
Cartons per layer	4
Cartons per pallet	20
Certifications and compliances	Argentina CNC; AS/NZ4268; AS/NZS 4268; AS/NZS 60950-1; AS/NZS 62368.1; Australia RCM; Australia/NZ RCM; Brazil ANATEL; CE Mark; CISPR22 Class B; CSA C22.2 No. 60950-1-07; CSA C22.2 No. 62368-1-14; EEA; EN 60950-1 & EN 62368-1; EN55024; EN61000-3-2, EN61000-3-3; EN55032 Class B; ETSI EN 300 328 v1.9.1; ETSI EN 301 489-1; ETSI EN 301 489-17; ETSI EN 301 489-3; FCC Part 15 (CFR 47) Class B; FCC Part 15C; FCC Part 15E; IEC 60950-1 & IEC 62368-1; ICES-003 Class B; Israel MOC; Japan MIC/VCCI; Malaysia SIRIM; NZ Telepermit; ROHS compliant; Saudi Arabia CITC; Singapore IMDA; So. Africa ICASA; So. Korea KC; Taiwan NCC/BSMI; UAE TRA; UL 60950-1 and UL 62368-1
Color	Black
Country of origin	Made in Laos
Dimensions (W x D x H)	33.9 x 29.4 x 6 cm
Display size (diagonal)	8.9 cm (3.5")
ECCN	5A992
Energy star certified	ENERGY STAR® certified
Headset and handset compatibility	Bluetooth® headset compatibility
HTS code	8517180050
Layers per pallet	5
Management Software	Poly Zero Touch Provisioning; RealPresence Resource Manager (v. 10.1 or above) based provisioning; Polycom Device Management Service for Enterprise (PDMS-E); Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management
Manufacturer product number	2200-66800
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT
Microphone type	Three cardioid microphones

Multiple order quantity	5
Network protocols, supported	DHCP VLAN discovery; LLDP-MED for VLAN discovery; FTP/TFTP/HTTP/HTTPS server-based central provisioning; Manual or dynamic host configuration protocol (DHCP) network setup; QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP; Time and date synchronization using SNTP; Provisioning and call server redundancy support
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Package dimensions (W x D x H)	1
Package weight	300 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
Panel technology	Monochrome LCD
Ports	1 RJ-45 (10/100/1000 Mbps)
Power	Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 0)
Products per pallet	100
Products per pallet layer	20
Registration required	No
Security management	802.1X Authentication and EAPOL Media encryption via SRTP; Digest authentication; Encrypted configuration files; HTTPS secure provisioning; Password login; Support for signed software executables; Support for URL syntax with password; Transport Layer Security (TLS); Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2); FIPS 140-2 compliant cryptographic module
Sensitivity (speaker)	90 dB
Special features	Adjustable base height; Unicode UTF-8 character support; Privacy shutter
Storage temperature range	-20 to 70 °C
Telephony and call handling features	Bundled with Polycom UC Software: Corporate Directory Access using LDAP; Call timer and call waiting; Call transfer, hold, divert (forward), park, pickup; Called, calling, connected party information; Distinctive incoming call treatment/call waiting; Do not disturb function; Local three-way audio conferencing; Local configurable digit map/dial plan; Shared call/bridged line appearance; Visual Conference Management; Up to 3 lines (maximum one Skype for Business and Microsoft Teams); Daisy-chain up to four; One-touch speed dial, redial and meeting join
UNSPSC code	43191511
UPC number	197497506273
VoIP features	IETF SIP (RFC 3261 and companion RFCs)
Weight	735 g

What's in the box Console; Network (LAN) cable-CAT-5E; Setup sheet

Wireless range Up to 3.7 m

Logistics

ECCN 5A992

HTS code 8517180050

UPC number 197497506273

What's in the box Console; Network (LAN) cable-CAT-5E; Setup sheet

Package dimensions (W x D x H) 1

Pallet dimensions (W x D x H) 101.6 x 121.9 x 149 cm

Dimensions (W x D x H) 33.9 x 29.4 x 6 cm

Country of origin Made in Laos

Cartons per layer 4

Cartons per pallet 20

Multiple order quantity 5

Layers per pallet 5

Products per pallet 100

Products per pallet layer 20

Manufacturer product number 2200-66800

Material Type for item FERT

UNSPSC code 43191511

Package weight 300 g

Pallet weight 357 kg

Weight 735 g

Specifications

[1] Optional power kit includes extended single-port gigabit midspan, 802.3af Type 2 compliant, local power cord and network cable (sold separately).

[2] Most software-enabled features and capabilities must be supported by the server. Please contact your IP PBX/Softswitch vendor or service provider for a list of supported features.

Legal disclaimer