

Poly Trio C60 IP Conference Phone for Microsoft Teams Full Radio and PoE-enabled

Active

849B6AA

NI

Specifications

All Specs

Aspect ratio	16:9
Audio	Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression; Comfort noise generation; DTMF tone generation (RFC 2833 and in-band); Low delay audio packet transmission; Adaptive jitter buffers
Audio codecs	G.711 (A-law and μ -law); G.722; G.722.1; G.722.1C; G.729AB; G.719; Polycom® Siren™ 7; Siren™ 14; iLBC; OPUS
Cartons per layer	4
Cartons per pallet	12
Certifications and compliances	AS/NZS 60950-1; AS/NZS 62368-1-17; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-1-14; CE Mark; CISPR22 Class B; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.9.1; ETSI EN 300 330; ETSI EN 301 893 v1.7.1; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1
Certified collaboration software	Microsoft Teams; Skype for Business
Color	Black
Country of origin	Made in China or Mexico
Dimensions (W x D x H)	38.3 x 7.5 x 33.2 cm
Display features	On-screen virtual keyboard
Display size (diagonal)	12.7 cm (5")
ECCN	5A992
End of Life CO2e (kg)	0.4
Energy star certified	ENERGY STAR® certified
Headset and handset compatibility	Bluetooth® headset compatibility
HTS code	8517180050
Layers per pallet	3
Management Software	Poly Zero Touch Provisioning; RealPresence Resource Manager (v. 10.1 or above) based provisioning; Polycom Device Management Service for Enterprise (PDMS-E); Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management; SDP
Manufacturer product number	2200-86670

Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT
Microphone type	Three cardioid microphones
Multiple order quantity	5
Native resolution	720 x 1280
Network protocols, supported	DHCP VLAN discovery; LLDP-MED for VLAN discovery; FTP/TFTP/HTTP/HTTPS server-based central provisioning; Manual or dynamic host configuration protocol (DHCP) network setup; QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP; Time and date synchronization using SNTP; Provisioning and call server redundancy support
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Package dimensions (W x D x H)	48.3 x 11.5 x 39.4 cm
Package weight	300 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
Panel technology	Color LCD
Ports	1 USB 2.0 Type-A (for USB battery charging); 1 USB 2.0 Micro-B (for USB audio device); 2 RJ-45 (10/100/1000BASE-TX Mbps)
Power	LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4); LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment
Production CO2e (kg)	52
Products per pallet	60
Products per pallet layer	20
Registration required	No
Security management	802.1X Authentication and EAPOL Media encryption via SRTP; Digest authentication; Encrypted configuration files; HTTPS secure provisioning; Password login; Support for signed software executables; Support for URL syntax with password; Transport Layer Security (TLS); Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2); FIPS 140-2 compliant cryptographic module
Sensitivity (speaker)	92 dB
Special features	Unicode UTF-8 character support
Storage temperature range	-20 to 70 °C

Telephony and call handling features	Bundled with Polycom UC Software: Corporate Directory Access using LDAP; Call timer and call waiting; Call transfer, hold, divert (forward), park, pickup; Called, calling, connected party information; Distinctive incoming call treatment/call waiting; Do not disturb function; Local configurable digit map/dial plan; Local five-way audio conferencing; Shared call/bridged line appearance; Visual Conference Management; Up to 3 lines (maximum one Skype for Business and Microsoft Teams); Daisy-chain up to four; One-touch speed dial, redial and meeting join
Total CO2e (kg)	70
Touch-enabled	Gesture-based, multi-touch capable touchscreen
Transportation CO2e (kg)	0.5
UNSPSC code	43191511
UPC number	(ABG) 197497506549; (UUF) 197498519159
VoIP features	IETF SIP (RFC 3261 and companion RFCs)
Weight	950 g
What's in the box	Setup sheet; Console; Network (LAN) cable-CAT-5E; Cable wrap; Tactile overlay for improved accessibility
Wireless range	Up to 6.1 m
Wireless technologies	Bluetooth® 4.2; Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20); 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

Logistics

ECCN	5A992
HTS code	8517180050
UPC number	(ABG) 197497506549; (UUF) 197498519159
What's in the box	Setup sheet; Console; Network (LAN) cable-CAT-5E; Cable wrap; Tactile overlay for improved accessibility
Package dimensions (W x D x H)	48.3 x 11.5 x 39.4 cm
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Dimensions (W x D x H)	38.3 x 7.5 x 33.2 cm
Country of origin	Made in China or Mexico
Cartons per layer	4
Cartons per pallet	12
Multiple order quantity	5
Layers per pallet	3

Products per pallet	60
Products per pallet layer	20
Manufacturer product number	2200-86670
Material Type for item	FERT
UNSPSC code	43191511
Package weight	300 g
Pallet weight	357 kg
Weight	950 g

Specifications

[1] Requires full Class 4 power input on LAN IN for operation

Legal disclaimer