

## Poly PoE++ 65W 2.5G Adapter with 3.66m CAT6A Cable and Power Cord

Active

B5NH6AA

NJ

### Specifications

#### All Specs

Cartons per layer	8
Cartons per pallet	40 (air); 56 (ocean)
Country of origin	Made in China
Dimensions (W x D x H)	90 x 51 x 28.5 mm
End of Life CO2e (kg)	0.5
Input frequency	50-60 Hz
Input operating current	2.0 A (maximum)
Input voltage	100-240 VAC
Layers per pallet	5 (air); 7 (ocean)
Manufacturer Warranty	Poly one-year limited warranty
Material Type for item	FERT
Multiple order quantity	10
Output voltages	56 Vdc
Package dimensions (W x D x H)	218 x 58 x 94 mm
Package weight	560 g
Pallet dimensions (W x D x H)	120 x 100 x 197.8 cm
Pallet weight	525.8 kg
Power	Meet IEEE 802.3af/at/bt
Production CO2e (kg)	71
Products per pallet	640 (air); 896 (ocean)
Products per pallet layer	60

Registration required	No
Total CO2e (kg)	100
Transportation CO2e (kg)	3
UNSPSC code	26121630
UPC number	198990106366
Weight	208 g
What's in the box	PoE++ Injector; Power cable; Cat 6A Ethernet cable (3.66 m)

### Logistics

UPC number	198990106366
What's in the box	PoE++ Injector; Power cable; Cat 6A Ethernet cable (3.66 m)
Package dimensions (W x D x H)	218 x 58 x 94 mm
Pallet dimensions (W x D x H)	120 x 100 x 197.8 cm
Dimensions (W x D x H)	90 x 51 x 28.5 mm
Country of origin	Made in China
Cartons per layer	8
Cartons per pallet	40 (air); 56 (ocean)
Multiple order quantity	10
Layers per pallet	5 (air); 7 (ocean)
Products per pallet	640 (air); 896 (ocean)
Products per pallet layer	60
Material Type for item	FERT
UNSPSC code	26121630
Package weight	560 g
Pallet weight	525.8 kg
Weight	208 g

---

[Legal disclaimer](#)