

Poly Sync 20+M Speakerphone USB-C/A Adapter

Active

B95VLAA

NG

Specifications

All Specs

| | |
|----------------------------------|--|
| Audio | Ideal for up to 4 x 4 m room size; Up to 2 m (7 ft) microphone pickup range; Full duplex audio; Noise and echo reduction; Bass reflect with dual passive radiators; Up to 7 ft / 2 m microphone pickup range |
| Battery life | Up to 20 hours (talk time) |
| Battery type | Rechargeable Li-ion |
| Bluetooth version | Bluetooth® Core 5.1 |
| Cable length | 715 mm |
| Cartons per layer | 10 |
| Cartons per pallet | 80 |
| Certifications and compliances | CE; CB; GS; FCC; IC; Rematel; IFT/NOM; RCM; MPTC; WPC; SDPPI; Telec/VCCI; KC; NTC; IMDA; SdoC; BSMI; NCC; SRRC; SIRIM; TRA; EAC; DWLF&F; TP-BY; MoC; TRC; Kvalitet; ICASA; UKCA; BOB; FSB; SONCAP; ICES; CULus; Ukraine; India BIS; KCC; VCCI; UL; CNC; TUV; ANRT; RATEL; IFETEL; DWLF&M; BIS; Telec; MOICT; iCTqatar; NOM; NBTC; CITRA; ETL; PAP Recycle Mark; WEEE; GreenDot; C-Tick; MCMC; UUF warning; ETA; Triman; CCC; cUL; Marocco CM |
| Certified collaboration software | Microsoft Teams certified; Google Meet certified |
| Charge time | <4 hours |
| Charging type | Cable |
| Color | Black |
| Compatibility | Compatible with PCs via USB Type-A cable and smartphones via Bluetooth® |
| Compatible Operating Systems | Windows 11; Windows 10; macOS |
| Connection type | Wireless: Bluetooth®, USB Type-C® BT700, USB Type-C®/A adapter |
| Connects to | PC; Mobile |
| Country of origin | China(AC3) |
| Dimensions (W x D x H) | 34 x 95 x 182 mm |
| End of Life CO2e (kg) | 0.1 |
| Impedance | 4 ohms |
| Indicator light | On call |

| | |
|--------------------------------|---|
| Layers per pallet | 8 |
| Management Software | Poly Lens |
| Manufacturer Warranty | Poly standard two-year limited warranty |
| Material Type for item | FERT |
| Microphone bandwidth | 100 Hz to 7.3 kHz |
| Microphone type | Three-microphone steerable array |
| Minimum System Requirements | USB Type-A port; Bluetooth®; USB Type-C® port |
| Nominal sound pressure level | 86 dB SPL |
| Number of microphones | 3 |
| Package dimensions (W x D x H) | 209 x 183 55 mm |
| Package weight | 0.54 kg |
| Paired devices | Up to 10 |
| Pallet weight | 456.52 kg |
| Production CO2e (kg) | 13 |
| Products per pallet | 800 |
| Products per pallet layer | 100 |
| Registration required | No |
| Sensitivity (microphone) | -20 dBV/Pa |
| Sensitivity (speaker) | 82 dB (1 W/1 m) |
| Signal-to-noise ratio | >68 dB |
| Speaker bandwidth | 80 Hz to 20 kHz |
| Speaker size | 40 mm |
| Supported bluetooth profiles | A2DP; AVRCP; HFP; HSP; BLE |
| Total CO2e (kg) | 10 |
| Transportation CO2e (kg) | 0.1 |

| | |
|-------------------|---|
| UNSPSC code | 43191515 |
| UPC number | 198990677187 |
| Weight | 360 g |
| What's in the box | Quick start guide; Warranty card; Product notice; Wired Speakerphone; Lanyard; Carrying pouch; BT700 Bluetooth® Type-C® adapter; USB Type-A adapter |
| Wireless range | Up to 30 m |

Logistics

| | |
|--------------------------------|---|
| UPC number | 198990677187 |
| What's in the box | Quick start guide; Warranty card; Product notice; Wired Speakerphone; Lanyard; Carrying pouch; BT700 Bluetooth® Type-C® adapter; USB Type-A adapter |
| Cable length | 715 mm |
| Package dimensions (W x D x H) | 209 x 183 55 mm |
| Dimensions (W x D x H) | 34 x 95 x 182 mm |
| Country of origin | China(AC3) |
| Cartons per layer | 10 |
| Cartons per pallet | 80 |
| Layers per pallet | 8 |
| Products per pallet | 800 |
| Products per pallet layer | 100 |
| Material Type for item | FERT |
| UNSPSC code | 43191515 |
| Package weight | 0.54 kg |
| Pallet weight | 456.52 kg |
| Weight | 360 g |

Specifications

[1] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

Legal disclaimer